



POWER SUPPLY SPECIFICATIONS:

1. INPUT VOLTAGE: 120VAC ±10% OR 240VAC ±10% SINGLE PHASE 50/60 Hz
2. 40°C MAXIMUM AMBIENT TEMPERATURE
3. 6" [154mm] CLEARANCE TO BE KEPT ON SIDES AND BACK FOR COOLING
4. NEMA 1 CORROSION RESISTANT
5. SEE THE FOLLOWING OUTLINE DRAWINGS FOR SEALING COIL DETAILS BG2070-12
6. STAND AND COIL MADE OF STAINLESS STEEL, NICKEL PLATED OR ANODIZED ALUMINUM, AND PLASTIC

THIS PRINT IS THE PROPERTY OF PILLAR TECHNOLOGIES AND IS LOANED TO THE RECIPIENT SUBJECT TO RETURN UPON DEMAND. ITS CONTENTS ARE CONFIDENTIAL AND MUST NOT BE COPIED OR REPRODUCED IN ANY MANNER WITHOUT THE WRITTEN PERMISSION OF PILLAR TECHNOLOGIES FOR USE OR EXAMINATION

REV	DESCRIPTION	APP'D	DATE
<p>PILLAR TECHNOLOGIES An ITW Company</p>			
<p>UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES 20 ±.005 OR 250 ±.005 OR 500 ±.005</p>		<p>REF DWG# CG2070-21 FILE NAME G2070-28 DATE 11-13-07 DRAWN BY EJU</p>	
<p>OUTLINE DRAWING UNIFOLIER 1KW-UC 5" WIDE x 6 FT LG CONVEYOR</p>			
<p>DWG NO G2070-28</p>		<p>SCALE 1" = 10" SHEET 1 OF 1</p>	