



- POWER SUPPLY SPECIFICATIONS:**
- INPUT VOLTAGE: 208 ±10% DR 240VAC ±10%; SINGLE PHASE 50/60 HZ
 - 40° C MAXIMUM AMBIENT TEMPERATURE
 - 6" [154mm] CLEARANCE TO BE KEPT ON SIDES AND BACK FOR COOLING
 - NEMA 1 CORROSION RESISTANT
- SEE THE FOLLOWING OUTLINE DRAWINGS FOR SEALING COIL DETAILS:
- UNIVERSAL COIL: BG2074-4
 CHANNEL COIL: BG2074-18
 STAND AND COIL MADE OF STAINLESS STEEL, ANODIZED ALUMINUM, AND PLASTIC

THIS PRINT IS THE PROPERTY OF
 PILLAR TECHNOLOGIES
 AND IS LOANED TO THE REQUESTOR SUBJECT TO
 RETURN UPON DEMAND. ITS CONTENTS ARE
 CONFIDENTIAL AND MUST NOT BE COPIED OR
 SUBMITTED TO OUTSIDE PARTIES FOR
 USE OR EXAMINATION

REV	DESCRIPTION	APP'D	DATE	REV	DESCRIPTION	DATE
C	ADDED METRIC DIMENSIONS	EJU	11-2-05			
B	ADDED COIL HEIGHT INDICATOR	RAK	1-20-05			
A	ADDED PLAN VIEW	RAK	2-17-04			

REV	DATE	FILE NAME	DESCRIPTION
CG2074-2	2074-12	CG2074-2	UNIVERSAL MODEL
RAK	2074-03	CG2074-2	UNIVERSAL MODEL
RAK	2074-03	CG2074-2	UNIVERSAL MODEL

SCALE	1 : 1
SHEET	1 of 1
DWG NO	CG2074-12
REV	C
PILLAR TECHNOLOGIES <small>A Division of Wipac Tools Inc</small> Hartford, Wisconsin 53029	
OUTLINE DRAWING UNIFOILER 2KW-U	