



POWER SUPPLY SPECIFICATIONS:

1. INPUT VOLTAGE: 240VAC ±10% SINGLE PHASE 50/60 HZ
2. 40°C MAXIMUM AMBIENT TEMPERATURE
3. 6" (154mm) CLEARANCE TO BE KEPT ON SIDES AND BACK FOR COOLING
4. NEMA 1 CORROSION RESISTANT
5. SEE THE FOLLOWING OUTLINE DRAWINGS FOR SEALING COIL DETAILS:
 - UNIVERSAL COIL: BG2074-4
 - CHANNEL COIL: BG2074-18
6. STAND AND COIL MADE OF STAINLESS STEEL, NICKEL PLATED OR ANODIZED ALUMINUM, AND PLASTIC

THIS PRINT IS THE PROPERTY OF
PILLAR TECHNOLOGIES
AND IS LOANED TO THE RECIPIENT SUBJECT TO
RETURN UPON DEMAND. ITS CONTENTS ARE
CONFIDENTIAL AND MUST NOT BE COPIED OR
REPRODUCED IN ANY MANNER FOR
USE OR EXAMINATION

REV	DESCRIPTION	APP'D	DATE
	FINISH		
	SPEC		

PILLAR TECHNOLOGIES An ITW Company		REF DWG# CG2074-13
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES 20 # OR 200 #, 90# 1000 #, 2000 #, 4000 #		FILE NAME: G2074-22
DRAWN BY: EJU		DATE: 11-13-07
TITLE: OUTLINE DRAWING UNIFOLIER 2KW-UC 5" WIDE x 6 FT LG CONVEYOR		SCALE: 1" = 10"
DWG NO: G2074-22		SHEET: 1 OF 1