

Unifoiler™ Complete Specification Reference

	1kW	1kW	2kW	4kW	6kW
INPUT:					
Voltage	120 VAC +/- 10%	240 VAC +/- 10%	208 or 240 VAC +/- 10%	240 VAC +10/-15%	240 VAC +10/-15%
	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
	1 phase	1phase	1 phase	3 phase	3 phase
Current					
at 120V	15.0 Amps				
at 240V		8.0 Amps	11.3 Amps	12.3 Amps	18.4 Amps
Power	1.6 kVa	1.6 kVa	2.7 kVa	5.1 kVa	7.65 kVa
OUTPUT:					
Current	6.0 Amps	6.0 Amps	11 Amps	15 Amps	18.3 Amps
Frequency	40 to 60 kHz	40 to 60 kHz	40 to 60 kHz	40 to 60 kHz	40 to 60 kHz
Power	1000 Watts	1000 Watts	2000 watts	4000 watts	6000 watts
Voltage	175 Vrms	175 Vrms			
low (SP1)				212 Vrms	261 Vrms
low (SP2)				310 Vrms	381 Vrms
low tap(H2)			268 Vrms	398 Vrms	489 Vrms
middle tap (H3)			350 Vrms	508 Vrms	625 Vrms
high tap (H4)			440 Vrms	610 Vrms	750 Vrms
Ambient Temperature:					
Maximum	105°F (40°C)	105°F (40°C)	105°F (40°C)	105°F (40°C)	105°F (40°C)

For outline drawings, features, benefits, options or to request an on-line quote, visit:

www.pillartech.com

